

ITEM # C1111

NAME OF ITEM: 2.4GHZ CAMERA WITH 2.0 USB RECEIVER

WIRELESS AND HIGH SPEED 2.0 USB TRANSMISSION MAKES THIS WIRELESS SYSTEM EASY TO USE & INSTALL

The 4-channel receiver and included software allows for direct USB connection to your computer for monitoring, motion activated recording or scheduled recordings. The receiver is powered via the USB connection.



Specifications:

Motion recording
 330TV lines
 USB2.0 output to PC and AV output to TV/Monitor
 Bundle with security software
 Image capture and high speed MPEG4 real-time recording
 Support MSN Messenger and Skype
 4 channels selectable
 300Ft LOS
 Windows 200/XP

INCLUDES

Wireless Camera	1
WIRELESS RECEIVER	1
Adapter for camera	1
Adapter for Receiver	1
ANTENNA	1
USB Cable & AV Cable	1
CD-ROM	1

Size

Camera: 23(W) x 66(D) x 23(H) mm excluding bracket

Receiver: 68(W) x 78(D) x 16(H) mm

Weight

Camera: 32g

Receiver: 119g

ITEM # C1111

NAME OF ITEM: 2.4GHZ CAMERA WITH 2.0 USB
RECEIVER

WIRELESS AND HIGH SPEED 2.0 USB TRANSMISSION
MAKES THIS WIRELESS SYSTEM EASY TO USE & INSTALL

TRANSMITTER	
Imaging Sensor	1/3 inch CMOS
CMOS Total Pixels	510 x 492
Horizontal Resolution	380
Minimum Illumination	5 Lux
Video Gain Control	Automatic
Frequency	10mW/CE; 2mW/FCC
Transmission Power	ISM 2,400 ~ 2,483 4CH
Modulation Mode	FM
Bandwidth	18 MHz
Power Supply	8VDC
Consumption Current	90 mA
Operating Temperature	-10 ~ +50 C / +14 ~ +122 F
Operating Humidity	85% RF
Dimensions	24(W) x 25(L) x 24(H) mm
Weight	14g
Unobstructed Effective Range	100m (min)

RECEIVER	
Receiving Frequency	ISM 2,400MHz ~ 2,483MHz
Intermediate Frequency	480MHz
Demodulation Type	FM
Antenna	50 ohm SMA
Receiving Sensitivity	≤ -85dBm
Video Output Signal Level	1.1V +/-0.2V @75 ohm, S/N >38dB
Power Supply	+5V
Consumption Current (Max.)	190mA
Unobstructed Effective Range	100m (min)
Dimensions	68(W) x 78(D) x 16(H) mm
Weight	119g
Operating Temperature	-10°C ~ +50°C / +14°F ~ +122°F
Operating Humidity	85% RH