

Cameras and DVRs

Low Light 1080P Button Camera (Item: CMD-BU20LX)

Lawmate has created a more secure camera connection. The Multipin twist on/off ensures the camera stays securely connected to the DVR at all times so evidence is never lost.

Features:

The CMD-BU20LX is a low light camera providing up to 1080P resolution with a wide dynamic range of light technology to provide the most accurate lighting adjustments for capturing clear visible footage in any situation. Hiding in plain sight is easy with this camera camera system. Simply install one of the button or screw lens covers to blend this high quality low light button camera into its natural environment. Whether the investigation is on-the-move or stationary, the quality of the footage is guaranteed with the **CMD-BU20LX**.



- Resolution: up to 1080P
- Sensor Resolution: 2.16M Pixels
- Video System: NTSC and PAL
- CMOS Camera
- Built-in image sensor: Progressive 1/2.8 inch Sony CMOS
- Sensitivity: .03 LUX @ F.2.0 50 IRE
- Angle of View: 78.2°
- Video Output: BT656 Data
- Audio Output: 2 Vp-p (MAX) 10 KHz ohms Impedance
- Microphone: 36 db (MAX)
- Power Supply: DC 3.3V
- Power Supply Current: 200mA
- Operating Temp: 14°F-140°F
- Storage Temp: -22°F-176°F
- Dimensions: 1" x 1" x .25" | Cord: 4.5 ft
- Weight: .35 oz.
- Compatible with HPV-1000EVO3

CMD-BU20LX features the ultra-secure connection which means this camera is only compatible with the **PV-1000EVO3**. This model DVR allows you to select the video resolution up to 1080P. Playback the video feed on the DVR or view live or remote playback with the PV Cam Viewer app. If WiFi is available where the camera is being set up, using the iP wireless connection allows the feed to be relayed anytime and anywhere a wireless or data connection is available on the paired device.

Tech Specs:

- Resolution: up to 1080P
- Low Light Button Camera
- Weight: .35 oz.
- Dimensions: 1 x 1 x .25 in | Cord: 4.5 ft
- Storage Temp: -22°F-176°F
- Operating Temp: 14°F-140°F

Cameras and DVRs

- Power Supply Current: 200mA
- Power Supply: DC 3.3V
- Microphone: 36 db (MAX)
- Data Audio Output: 2 Vp-p (MAX) 10 KHz ohms Impedance
- Video Output: BT656
- Angle of View: 78.2°
- Sensitivity: .03 LUX @ F.2.0 50 IRE
- Built-in image sensor: Progressive 1/2.8 inch Sony CMOS
- CMOS Camera
- Video System: NTSC and PAL
- Sensor Resolution: 2.16M Pixels

Includes:

- Button Camera
- Button Accessories

