Cameras and DVRs

VPC 2.0 Video Pole Camera (Item: VPC 2.0)

Expand your visual inspection capabilities REI's new VPC 2.0 Video Pole Camera extends the view of surroundings, above drop ceilings, behind immovable objects, around corners or other difficult to reach areas, even in dark situations.







REI the premier maker of TSCM equipment has super charged the Pole Camera market place!

- Large 8 inch (20.3 cm), high-resolution color monitor.
- No external cables, ready-to-use out of the case.
- Portable, lightweight case for easy mobility.
- Motorized Tilt Camera head
- Video Record and playback
- Still picture capture and review it
- · LEDs mounted on the camera
- Choose 1- Color camera head includes white LED illumination for color inspection in dark areas or IR LED illuminated black and white camera head available for covert applications.
- Weatherproof body
- 8" high tilting LCD display with brightness control
- The VPC 2.0 extends to 6 ft 5 in.(198 cm), giving the average user over 10 ft (3 m) of reach.

Applications, Inspecting high drop ceilings, searching over-head compartments, vehicle undercarriages, viewing around corners, over tall or immovable objects, viewing difficult to reach areas.

Need more reach and both cameras see the VPC 2.0 Deluxe

Tech Specs:

- Color Camera Head(standard) Signal Format: NTSC Horizontal Resolution: 550 TV Lines, Sensitivity: 0.5 Lux / Faceplate Illumination: White LEDs with variable brightness control
- Black & White Camera Head Signal Format: NTSC Horizontal



Cameras and DVRs

Resolution: 600 TV Lines Sensitivity: 0.1 Lux / Faceplate Illumination: Infrared LEDs with variable brightness control

- Color LCD Display Size: 8"Resolution: 800x600 Auto Brightness Viewing Angles: (70° at 3, 9, & 6 o'clock) (50° at 12 o'clock) Display Controls: Color saturation, contrast, & brightness Camera
- DVR:Format: MPEG 25fps Record Time: 5s, 10s, 30s, 60s, & 120s On-screen Date and Time Stamp Video Playback Mode Snapshot Mode: 720x480 jpg
- Miscellaneous: Video Output Jack Audio Output Jack Micro SD Card Slot Internal Battery Charger 2 Lithium Ion Batteries: (included)
 Typical Run Time: 5 Hours Max Charge Time: 3 Hours
- Mechanical:Collapsed length (with Camera Head): 23.5 in (59.7 cm) Extended Length (with Camera Head): 78 in (198 cm) Case Size: 20x15x5 in (50x38x14 cm) Case Weight (with all accessories): 12 lbs (5.4

Includes:

- 1 Camera Head (Choice of Either Color or IR-Black-and-White)
- 3.5mm to RCA Video Output Cable
- Battery Pack (2) Rechargeable Lithium-Ion Batteries AC Power Supply Includes 3 adapters for International charging
- 8 Gb Micro SD Card
- Standard Length Pole and Monitor Assembly



